PATENT Atty. Dkt. No. ROC920010046US1 MPS Ref. No.: IBM/K10046.Y1

IN THE CLAIMS:

- (Currently Amended) A method for processing multimedia data, comprising: indexing the multimedia data to an i by j matrix; and
- storing a plurality of odd/even index sequences of the i by j matrix in a data storage device on a hard disk drive having a plurality of logic blocks, wherein at least two odd/even index sequences are stored in separate logic blocks of the hard disk drive.
- 2. (Original) The method of claim 1 wherein the multimedia data is selected from still image data and video image data.
- 3. (Currently Amended) The method of claim 24, further comprising disabling a data recovery procedure programmed on the data-storage-device, wherein the data-storage-device comprises a hard disk drive.
- 4. (Original) The method of claim 1 wherein the multimedia data represents an image having i times j pixels.
- 5. (Original) The method of claim 1 wherein the multimedia data represents an image having i times j subimages and wherein the i by j matrix corresponds to the i times j subimages.
- 6. (Currently Amended) The method of claim 24, wherein the multimedia data represents an image having i times j subimages and wherein the i by j matrix corresponds to the i times j subimages; further comprising:

compressing the subimages before storing the i by j matrix in the data storage device on the hard disk drive; and

decompressing the reconstructed i by j matrix to render the image.

PATENT Atty. Dkt. No. ROC920010046US1 MPS Ref. No.: IBM/K10046.Y1

- 7. (Currently Amended) The method of claim 1 wherein the plurality of odd/even index sequences comprises an odd/odd index sequence, an odd/even index sequence, an even/odd index sequence, and an even/even index sequence, wherein at least two odd/even index sequences are stored in separate legic blocks in a hard disk drive.
- 8. (Currently Amended) The method of claim 7 wherein the index sequences are stored in logic blocks in the data storage device on the hard disk drive and wherein each of the index sequences is separately stored in respective logic blocks.
- 9. (Currently Amended) The method of claim 7 wherein each index sequence is stored in one or more logic blocks in the data storage device on the hard disk drive and wherein each logic block contains portions of at most two different index sequences.
- 10. (Currently Amended) The method of claim 24.

wherein the plurality of odd/even index sequences comprises an odd/odd index sequence, an odd/even index sequence, an even/odd index sequence, and an even/even index sequence;

wherein each index sequence is stored separately in one or more logic blocks in the data sterage device on the hard disk drive;

wherein the reconstructing step further comprises further comprising, when a logic block is flawed, assigning one or more fixed values for replacing data contained in one or more portions of the index sequences contained in the flawed logic block with one or more fixed values.

11. (Currently Amended) The method of claim 24,

wherein the plurality of odd/even index sequences comprises an odd/odd index sequence, an odd/even index sequence, an even/odd index sequence, and an even/even index sequence:

PATENT
Alty. Dkt. No. ROC920010046US1
MPS Ref. No.: IBM/K10046.Y1

wherein each index sequence is stored separately in one or more logic blocks in the data storage device on the hard disk drive;

wherein the reconstructing step further comprises further comprising, when a logic block is flawed, interpolating one or more replacement values for one or more portions of the index sequences contained in the flawed logic block.

12. (Currently Amended) A signal bearing medium, comprising a program which, when executed by a processor, performs a method comprising:

indexing the multimedia data to an i by j matrix; and

storing a plurality of odd/even index sequences of the i by j matrix in a data storage device on a hard disk drive having a plurality of logic blocks, wherein at least two odd/even index sequences are stored in separate logic blocks of the hard disk drive.

- 13. (Currently Amended) The signal bearing medium of claim 25, wherein the method further comprises disabling a data recovery procedure programmed on the data storage device, wherein the data storage device comprises a hard disk drive.
- 14. (Original) The signal bearing medium of claim 12 wherein the multimedia data represents an image having i times j subimages and wherein the i by j matrix corresponds to the i times j subimages.
- 15. (Currently Amended) The signal bearing medium of claim 25, wherein the multimedia data represents an image having i times j subimages, wherein the i by j matrix corresponds to the i times j subimages, and wherein the method further comprises:

compressing the subimages before storing the i by j matrix in the data storage device on the hard disk drive; and

decompressing the reconstructed i by j matrix to render the image.

PATENT Alty. Dkt. No. ROC920010046US1 MPS Ref. No.: IBM/K10046.Y1

- 16. (Currently Amended) The signal bearing medium of claim 12 wherein the plurality of odd/even index sequences comprises an odd/odd index sequence, an odd/even index sequence, an even/odd index sequence, and an even/even index sequence, wherein at least two odd/even index sequences are stored in separate logic blocks in a hard disk drive.
- 17. (Currently Amended) The signal bearing medium of claim 16 wherein each index sequence is stored in one or more logic blocks in the data storage device on the hard disk drive and wherein each logic block contains portions of at most two different index sequences.
- 18. (Currently Amended) The signal bearing medium of claim 25,

wherein the plurality of odd/even index sequences comprises an odd/odd index sequence, an odd/even index sequence, an even/odd index sequence, and an even/even index sequence;

wherein each index sequence is stored separately in one or more logic blocks in the data storage device on the hard disk drive; and

wherein the reconstructing step of the method further comprises, when a logic block is flawed, interpolating one or more replacement values for one or more portions of the index sequences contained in the flawed logic block.

- 19. (Currently Amended) <u>An apparatus A server system</u> for processing multimedia data, comprising:
 - a processor;
 - a memory connected to the processor, and

one or more storage devices for storing multimedia data connected to the processor, wherein the processor is configured to perform a method for processing multimedia data, comprising:

indexing the multimedia data to an i by j matrix; and

storing a plurality of odd/even index sequences of the i by j matrix in-a data storage device on a hard disk drive having a plurality of logic blocks, wherein at

Page 5

Atly. Dkt. No. RQC920010046US1 MPS Ref. No.: IBM/K10046,Y1

least two odd/even index sequences are stored in separate logic blocks of the hard disk drive.

- 20. (Currently Amended) The system apparatus of claim 26 wherein the processor is further configured to disable a data recovery procedure programmed on the data storage device, wherein the data storage device comprises a hard disk drive.
- 21. (Currently Amended) The system apparatus of claim 19 wherein the plurality of odd/even index sequences comprises an odd/odd index sequence, an odd/even index sequence, an even/odd index sequence, and an even/even index sequence, wherein at least two odd/even index-sequences are stored in separate logic blocks in a hard disk drive.
- The eyetem apparatus of claim 21 wherein the 22. (Currently Amended) processor is further configured to store each index sequence in one or more logic blocks in the data storage device on the hard disk drive and wherein each logic block contains portions of at most two different index sequences.
- 23. The system apparatus of claim 26, (Currently Amended)

wherein the plurality of odd/even index sequences comprises an odd/odd index sequence, an odd/even index sequence, an even/odd index sequence, and an even/even index sequence;

wherein the processor is further configured to store each index sequence separately in one or more logic blocks in the data storage device on the hard disk drive; and

wherein, when reconstructing the matrix, the processor is further configured to interpolate one or more replacement values, when a logic block is flawed, for one or more of the index sequences contained in the flawed logic block.

The method of claim 1, further comprising: 24. (Currently Amended)

Page 6

PATENT Atty. Dkt. No. ROC920010046US1 MPS Ref. No.: IBM/K10046,Y1

retrieving data comprising the stored index sequences from the data storage device hard disk drive; and

reconstructing the i by j matrix utilizing odd/even index sequencing of the retrieved data.

25. (Currently Amended) The signal bearing medium of claim 12, wherein the method further comprises:

retrieving data comprising the stored index sequences from the data storage device hard disk drive; and

reconstructing the i by j matrix utilizing odd/even index sequencing of the retrieved data.

26. (Currently Amended). The system apparatus of claim 19, wherein the processor is further configured to retrieve data comprising the stored index sequences from the data storage device hard disk drive and to reconstruct the i by j matrix utilizing odd/even index sequencing of the retrieved data.

Please add the following claims:

27. (New) A method for processing multimedia data, comprising:

retrieving data from a data storage device, wherein the data comprises a plurality of odd/even index sequences of an i by j matrix representing multimedia data, wherein at least two odd/even index sequences are stored in at least two respective logic blocks on a hard disk drive; and

reconstructing the i by j matrix utilizing odd/even index sequencing of the retrieved data.

28. (New) The method of claim 27, further comprising disabling a data recovery procedure programmed on the hard disk drive, and wherein the reconstructing step further comprises, when a logic block is flawed, replacing data contained in one or

Page 7

PATENT Alty. Dkt. No. ROC920010048US1 MPS Ref. No.: IBM/K10046.Y1

more portions of the index sequences contained in the flawed logic block with at least one of a fixed value and an interpolated value.